

# RUMEX CK-4 SAE 15W/40

HEAVY DUTY ENGINE OIL

**DYADE**  
LUBRICANTS

320203001



## HEAVY DUTY ENGINE OIL

This is a LOW SAPS heavy duty engine oil of the latest generation. This product meets a variety of specifications and is specifically developed in order to have total engine protection at extreme long interval ranges. This product has a high shear resistance and operates very well in a very broad operating temperature range. This product can be used in off-road and on-road heavy duty applications and is suitable for the newer and more traditional vehicle portfolio. It can be used in vehicles with and without turbocharges or after treatment devices. Very high levels of fuel economy are met with this product. This product is compatible with emission control technology EURO IV, EURO V, and VI.

## FUEL ECONOMY RATING



## SPECIFICATIONS

|                    |                           |                      |
|--------------------|---------------------------|----------------------|
| ACEA E11           | CUMMINS CES 20081         | MAN M3775            |
| ACEA E9-16         | CUMMINS CES 20086         | MB 228.31            |
| ALLISON C4         | DAIMLER TRUCK DTFR 15C100 | MB 228.31            |
| API CI-4           | DETROIT DIESEL DFS 93K222 | MTU OIL CATEGORY 2.1 |
| API CI-4 PLUS      | DEUTZ DQC-III-10 LA       | RENAULT RGD          |
| API CJ-4           | DEUTZ DQC-III-18 LA       | RENAULT RLD          |
| API CK-4 / SN      | FORD WSS-M2C171-F1        | RENAULT RLD-2        |
| CASE MAT 3571      | JASO DH-2                 | RENAULT RLD-3        |
| CASE MAT 3572      | JD JDQ-78X                | RENAULT RLD-4        |
| CATERPILLAR ECF-1A | MACK EO-M PLUS            | RENAULT RXD          |
| CATERPILLAR ECF-2  | MACK EO-N                 | VOLVO VDS-3          |
| CATERPILLAR ECF-3  | MACK EO-N PREMIUM PLUS    | VOLVO VDS-4          |
| CATERPILLAR TO-2   | MACK EO-O PREMIUM PLUS    | VOLVO VDS-4.5        |
| CUMMINS CES 20076  | MACK EO-S 4.5             |                      |
| CUMMINS CES 20077  | MACK EO-S 4.5             |                      |
| CUMMINS CES 20078  | MAN M3575                 |                      |

| GRADE                        | METHOD     | UNIT     | VALUE |
|------------------------------|------------|----------|-------|
| Density                      | ASTM D4052 | kg/l     | 0,86  |
| Kinematic viscosity @ 40 °C  | ASTM D445  | mm²/s    | 92,5  |
| Kinematic viscosity @ 100 °C | ASTM D445  | mm²/s    | 13,7  |
| Viscosity Index              | ASTM D2270 |          | 150   |
| B.N. (HCL04 method)          | ASTM D2896 | mg KOH/g | 9,5   |
| Pour point                   | ASTM D6892 | °C       | -42   |
| Flash point                  | ASTM D92   | °C       | 226   |
| Sulphated ash content        | ASTM D874  | %        | 1     |

All data on this technical data sheet is indicative only

202401V01



## Product information

People buy this product because they need the newest CK-4 HD engine oil

### CATEGORY

- Heavy Duty
- Engine Oil

### BASE OIL

- Mineral

### AVAILABLE PACKAGING

- 12x1 L
- 5x4 L
- 4x5 L
- 20 L
- 60 L
- 205 L
- 1000 L

MAINTAIN THE THINGS WE VALUE, WHILE MAKING THE WORLD A CLEANER PLACE

DYADE LUBRICANTS B.V.  
TYPOGRAAF 16 | 6921 VB DUIVEN  
THE NETHERLANDS

0031 (0) 316 745 745  
INFO@DYADE-LUBRICANTS.COM  
WWW.DYADEGLOBAL.COM